

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/059521 A1

(51) International Patent Classification⁷: G01N 3/32

(21) International Application Number:
PCT/EP2004/053313

(22) International Filing Date: 7 December 2004 (07.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03405890.9 11 December 2003 (11.12.2003) EP

(71) Applicant (for all designated States except US): EID-
GENÖSSISCHE TECHNISCHE HOCHSCHULE
ZÜRICH [CH/CH]; ETH transfer, Rämistrasse 101,
CH-8092 Zürich (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MAZZA, Edoardo
[CH/CH]; Ellenbergstrasse 5, CH-8112 Otelfingen

(CH). VALTORTA, Davide [IT/CH]; Kurvenstrasse 11,
CH-8600 Dübendorf (CH). VOLLMANN, Jacqueline
[CH/CH]; Schaffhauserstrasse 129, CH-8057 Zürich (CH).


(74) Agent: RENTSCH UND PARTNER; Fraumünster-
strasse 9 Postfach 2441, CH-8022 Zürich (CH).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: DEVICE AND METHOD FOR MEASURING FLEXURAL DAMPING OF FIBRES



(57) Abstract: The present invention is directed to a device and a method for measuring flexural damping in fibres (1). The device comprises a transducer (6), at which transducer (6) the fibre (1) is attachable with one of its extremities. For the measurement said transducer (6) induces flexural vibration into the fibre (1). Further a light barrier (4) built by a light emitter (2) and a light receiver (3) arranged in line to each other and approximately perpendicular to the attachable fibre (1), thus that a light beam (5) emitted by the light emitter (2) and received by the light receiver (3) is periodically interrupted by the fibre (1) during vibration and the phase delay between excitation signal and fibre response is obtainable from the electrical signal of the interrupted light beam (5).



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*